LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

N/A = Not Applicable

1. Name of cel	1. Name of cell / battery						
Lithium ion	Lithium ion Battery JH651419						
2. Manufacture	er of cell / baltery		<u> </u>				
Name	Guangshou Yicheng Battery Co Ltd						
Address	Cuangenes from the gradery of the						
Phone							
Email							
Website							
3. Test laboratory of cell / battery							
Name Shenzhen Beihang Testing Co. Ltd							
Address	Chonenon Domaing 100mg 001 and						
Phone							
Email							
Website	Website						
4. ID-number	and date						
Unique test rep			Date of test r	eport 2018/07/21			
DESCRIPTION OF CELL / BATTERY							
5. Mark the ty	ype of cell/battery with an	"•"					
Lithium ion cell			Lithium metal cell				
X Lithium ion battery		Lithium metal battery					
Lithium hybrid battery							
6. Parameters			Cell		Baltery		
Mass in gram (g):			2000		8,9		
Lithium ion: Indicate watt-hour rating (Wh):					1,11		
Lithium metal: Indicate lithium metal content in gram (g):							
Lithium hybrid: Indicate lithium metal content in gram (g) and watt-hour rating (Wh):						g	
Lithium nybrid	J. Mulicate utilium metal col		u watt-nour rath	9 (***11).			Wh

LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name of cell/battery (taken from field 1)

Polymer lithium ion Battery

7. Physical description of cell / battery					
prismatic					
	we allow this complete the street	- North Control of the Control of th			
8. Model numbers					
23840 Motion					
TESTS AND RESULTS					
9. List of tests conducted and results - Mark N/A, pass or fail with an "●"	N/A	pass	fail		
T1 - Altitude simulation		0			
T2 - Thermal Test		0	0		
T3 - Vibration		0	0		
T4 - Shock	0	0	0		
T5 - External Short Circuit	0	0	0		
T6 - Impact / Crush	0	0	0		
T7 - Overcharge	0	0	Q		
T8 - Forced Discharge	0	0	O		
for all above	0	\otimes	0		
	0	0			
10. Reference to assembled battery testing requirements					
	N/A				
11. Reference to the revised edition of the Manual of Tests and Criteria used and to amendments thereto					
The resistance to the resisted edition of the manager resistant and strength and to amount the resistance to the resistance of the resista					



LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name of cell/battery (taken from field 1)

Polymer lithium ion Battery

ADDITIONAL SUPPLIER INQUIRY

12. Quality management system for manufacturing cells / batteries Does the manufacturer of the cell/battery manufacture the products based on a documented quality management system according to transport regulations?	X	YES	NO
13. Are the following parameters exceeded? Lithium ion cell: more than 20 Wh Lithium ion battery: more than 100 Wh Lithium metal cell: more than 1 g Lithium Lithium metal battery: more than 2 g Lithium Lithium hybrid Battery: more than 1,5 g Lithium and/or more than 10 Wh	\bigcirc	YES	NOX
Check point 14 – 16 need to be answered when 13 has been ticked "YES":			
14. Does each cell / battery incorporates a safety venting device or is designed to preclude a violent rupture under normal conditions of carriage?		YES	NO
15. Is each cell / battery equipped with an effective means of preventing external short circuits?	0	YES	NO O
16. Is each battery containing cells or series of cells connected in parallel equipped with effective means as necessary to prevent dangerous reverse current flow (e.g. diodes, fuses, etc.)?		YES	NO

 Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion cells/batteries and lithium polymer cells/batteries 			
State of Charge (SoC) max. 30 %	0	YES	NO O

CELLS/BATTERIES INSTALLED IN EQUIPMENT

18. Check point 18 needs to be answered when the cells / batteries are installed in articles:						
18.a) Only button cells enclosed?					NO	X
18.b) Number of enclosed cells (other than button cells)/batteries per equipment						
Enclos	sed batt	eries p	er equip	oment	1	
When the equipment is intentionally active/switched on during transport e.g. data loggers:						
18.c) Confirmation that no dangerous amount of heat is emitted from the equipment X N/A YES					NO	
18.d) Confirmation that the equipment when transported by air fulfills the defined air transport standards for electromagnetic radiation according to DO-160			YES	NO		
1	tteries per equipment Enclos uring transport e.g. date ed from the equipment air fulfills the defined	Enclosed bate spring transport e.g. data logge and from the equipment are fulfills the defined	Enclosed batteries puring transport e.g. data loggers: ed from the equipment X N/A air fulfills the defined	Enclosed batteries per equipment Enclosed batteries per equipment viring transport e.g. data loggers: Enclosed batteries per equipment viring transport e.g. data loggers: Enclosed batteries per equipment viring transport e.g. data loggers:	tteries per equipment Enclosed batteries per equipment uring transport e.g. data loggers: ed from the equipment X N/A YES air fulfills the defined	tteries per equipment Enclosed batteries per equipment In transport e.g. data loggers: Enclosed batteries per equipment In transport e.g. data loggers: In trans

19. Place, Date	20. Title, Surname, First name	21. Company stamp and signature
Bünde, 2019.11.26	Vieregge Thomas Head of Quality Assurance & Product Safty	11 - 11 1000000 065-0
		Tel.: (+49/0) 5223

