LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

N/A = Not Applicable

| 1. Name of cell / baltery | | | | | | |
|---|---|------|--------------------|-----------|---------|--|
| Lithium ion Polymer Cell HC501419KZ | | | | | | |
| 2. Manufacturer of cell / battery | | | | | | |
| Name | Nanyang Huachuang New Energy Co Ltd | | | | | |
| Address | | | | | | |
| Phone | | | | | | |
| Email | | | | | | |
| Website | | | | | | |
| 3. Test laborat | ory of cell / battery | | • | | | |
| Name | | | | | | |
| Address | L. | | | | | |
| Phone | | | | | | |
| Email | | | | | | |
| Website | | | | | | |
| 4. ID-number | and date | | | | | |
| MATERIAL STATE OF THE STATE OF | ort identification number TCT190109B | 006 | Date of test re | eport 201 | 9/01/21 | |
| DESCRIPTION OF CELL / BATTERY | | | | | | |
| 5. Mark the type of cell/battery with an "•" | | | | | | |
| X Lithium ion cell | | | Lithium metal cell | | | |
| Lithium ion battery | | Liti | hium metal I | pattery (| | |
| Lithium hybrid battery | | | | | | |
| 6. Parameters | | | Cell | Battery | | |
| Mass in gram (g): | | | | 3 | | |
| Lithium ion: Indicate watt-hour rating (Wh): | | | | 0,28 | | |
| Lithium metal: Indicate lithium metal content in gram (g): | | | | | | |
| Lithium hybrid | Lithium hybrid: Indicate lithium metal content in gram (g) and watt-hour rating (Wh): | | | | | |
| Wh | | | | | | |

LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name of cell/battery (taken from field 1)

Polymer lithium ion Battery

| 7. Physical description of cell / battery | | | | | |
|---|-----|-----------|----------|--|--|
| prismatic | | | | | |
| • | | | | | |
| 8. Model numbers | | | | | |
| 23841 Toxi | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| TECTS AND DESIRES | | | | | |
| TESTS AND RESULTS | _ | | T | | |
| 9. List of tests conducted and results - Mark N/A, pass or fail with an "•" | N/A | pass | fail | | |
| T1 - Altitude simulation | Q | Q | Q | | |
| T2 - Thermal Test | Q | Q | Q | | |
| T3 - Vibration | Q | Q | Q | | |
| T4 - Shock | Q | Q | Q | | |
| T5 - External Short Circuit | O | 0 | 0 | | |
| T6 - Impact / Crush | O | 0 | 0 | | |
| T7 - Overcharge | 0 | 0 | O | | |
| T8 - Forced Discharge | 0 | 0 | 0 | | |
| for all above | 0 | \otimes | 0 | | |
| | 0 | 0 | 0 | | |
| | | | | | |
| 10. Reference to assembled battery testing requirements | | | I | | |
| | | | | | |
| | | | N/A | | |
| | | | | | |
| | | | | | |
| 11. Reference to the revised edition of the Manual of Tests and Criteria used and to amendments thereto | | | | | |
| | | | | | |
| | | | | | |

LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name of cell/battery (taken from field 1)

Polymer lithium ion Battery

ADDITIONAL SUPPLIER INQUIRY

| 12. Quality management system for manufacturing cells / batteries Does the manufacturer of the cell/battery manufacture the products based on a documented quality management system according to transport regulations? | | | NO | | | |
|---|------------|-----|-------|--|--|--|
| | | | | | | |
| 13. Are the following parameters exceeded? Lithium ion cell: more than 20 Wh Lithium ion battery: more than 100 Wh Lithium metal cell: more than 1 g Lithium Lithium metal battery: more than 2 g Lithium Lithium hybrid Battery: more than 1,5 g Lithium and/or more than 10 Wh | \bigcirc | YES | NOX | | | |
| | | | | | | |
| Check point 14 – 16 need to be answered when 13 has been ticked "YES": | | | | | | |
| 14. Does each cell / battery incorporates a safety venting device or is designed to preclude a violent rupture under normal conditions of carriage? | | YES | NO | | | |
| 15. Is each cell / battery equipped with an effective means of preventing external short circuits? | 0 | YES | NO ON | | | |
| 16. Is each battery containing cells or series of cells connected in parallel equipped with effective means as necessary to prevent dangerous reverse current flow (e.g. diodes, fuses, etc.)? | | YES | NO | | | |
| | | | | | | |
| Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion cells/batteries and lithium polymer cells/batteries | | | | | | |
| State of Charge (SoC) max. 30 % | 0 | YES | NO ON | | | |
| | | | | | | |

CELLS/BATTERIES INSTALLED IN EQUIPMENT

| 18. Check point 18 needs to be answered when the cells / batteries are installed in articles: | | | | | | | | |
|---|------------------------------|--------|---------|----------|----------|-------|----|---|
| 18.a) Only button cells enclosed? | | | | | X | YES | NO | 0 |
| 18.b) Number of enclosed cells (other than button cells)/batteries per equipment | | | | | | | | |
| | Enclosed cells per equipment | Enclos | ed batt | eries pe | er equip | oment | 1 | |
| When the equipment is intentionally active/switched on during transport e.g. data loggers: | | | | | | | | |
| 18.c) Confirmation that no dangerous amount of heat is emitted from the equipment X N/A YES | | | | | NO | | | |
| 18.d) Confirmation that the equipment when transported by air fulfills the defined air transport standards for electromagnetic radiation according to DO-160 X N/A YES | | | | | NO | | | |

| Bünde, 2019.11.27 Vieregge Thomas Head of Quality Assurance & Product Safty Revell GmbH | 19. Place, Dale | 20. Title, Surname, First name | 21. Company stamp and signature |
|--|-------------------|--|--|
| J/2007 7 7 | Bünde, 2019.11.27 | Vieregge Thomas Head of Quality Assurance & Product Safty | Revell GmbH Revell GmbH Revell GmbH Revell GmbH |

√32257 Bun .3 Tel.: (+49/0) 3223 365-0

