LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

N/A = Not Applicable

1. Name of cel	ll / battery	-					
Lithium ion	battery 802035						
2. Manufacture	er of cell / battery						
Name	Guangzhou Yich	eng Battery Co	Ltd				
Address							
Phone							
Email							
Website							
3. Test laborat	ory of cell / baltery						
Name	Shenzhen Beihan	g-TestingCo. Lt	d				
Address							
Phone							
Email							
Website							
		3					
4. ID-number	and date	•			···		
Unique test rep	ort identification number	RSZBHST180	315114	Date of test	report	2018	3/03/19
DESCRIPTIO	N OF CELL / BATTER	ξΥ :				-	
5. Mark the ty	pe of cell/battery with an	"•"	-				
Lithium	ion cell		32		Lithiu	m meta	al cell O
X Lithium	X Lithium ion battery The Lithium metal battery			attery O			
Lithium	hybrid battery						
6. Parameters	3				Cell		Battery
Mass in gram (Mass in gram (g):						10,8
Lithium ion: Inc	Lithium ion: Indicate watt-hour rating (Wh):						1,4
Lithium metal:	Indicate lithium metal con	tent in gram (g):					

Lithium hybrid: Indicate lithium metal content in gram (g) and watt-hour rating (Wh):

LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name of cell/battery (taken from field 1)

Polymer lithium ion Battery

7. Physical description of cell / battery					
prismatic					
8. Model numbers					
23842 GoStunt					
TESTS AND RESULTS					
	Ţ	***************************************			
9. List of tests conducted and results - Mark N/A, pass or fail with an "•"	N/A	pass	fail		
T1 - Altitude simulation	Q	Q	Q		
T2 - Thermal Test	Q	Q	Q		
T3 - Vibration	Q	0	O		
T4 - Shock	Q	Q	Q		
T5 - External Short Circuit	O	0	O		
T6 - Impact / Crush	O	O	0		
T7 - Overcharge	0		0		
T8 - Forced Discharge	0	0			
for all above	0	\otimes			
	0	0			
10 Personal and a second of the second of th		anor analy to success			
10. Reference to assembled battery testing requirements					
			N/A		
11. Reference to the revised edition of the Manual of Tests and Criteria used and to amendments thereto					
The Reference to the revised edition of the Manual or Tests and Criteria used and	u to amename	nts thereto			

LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3
OF MANUAL OF TESTS AND CRITERIA

Name of cell/battery (taken from field 1)

Polymer lithium ion Battery

ADDITIONAL SUPPLIER INQUIRY

12. Quality management system for manufacturing cells / batteries Does the manufacturer of the cell/battery manufacture the products based on a documented quality management system according to transport regulations?	X	YES	NO
13. Are the following parameters exceeded? Lithium ion cell: more than 20 Wh Lithium ion battery: more than 100 Wh Lithium metal cell: more than 1 g Lithium Lithium metal battery: more than 2 g Lithium Lithium hybrid Battery: more than 1,5 g Lithium and/or more than 10 Wh		YES	NO
Check point 14 – 16 need to be answered when 13 has been ticked "YES":			
14. Does each cell / battery incorporates a safety venting device or is designed to preclude a violent rupture under normal conditions of carriage?		YES	NO
15. Is each cell / battery equipped with an effective means of preventing external short circuits?	0	YES	NO O
16. Is each battery containing cells or series of cells connected in parallel equipped with effective means as necessary to prevent dangerous reverse current flow (e.g. diodes, fuses, etc.)?	0	YES	NO
 Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion cells/batteries and lithium polymer cells/batteries 			
State of Charge (SoC) max. 30 %		YES	ио 🔵
			hara and a second

CELLS/BATTERIES INSTALLED IN EQUIPMENT

18. Check point 18 needs to be answered when the cells / ba	tteries are installed	in artic	cles:	***************************************		***************************************	
18.a) Only button cells enclosed?		***************************************			YES	NO ()	0
18.b) Number of enclosed cells (other than button cells)/batteries per equipment							
Enclosed cells per equipment	Enclosed batteries per equipment			1			
When the equipment is intentionally active/switched on during transport e.g. data loggers:						-	
18.c) Confirmation that no dangerous amount of heat is emitted from the equipment X N/A YES NO							
18.d) Confirmation that the equipment when transported by air air transport standards for electromagnetic radiation acc	fulfills the defined ording to DO-160	X	N/A		YES	NO	

19. Place, Date	20. Title, Surname, First name	21. Company stamp and signature
Bünde, 2019.11.27	Vieregge Thomas Head of Quality Assurance & Product Safty	Revell GmbH A Heastheistr. 20-30 Heastheistr. Runde

7/25/ Bunde Tel.: (+49/0) 5223 965-0