LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

N/A = Not Applicable

1. Name of cell / batte	241	_		A		
						Verein privile in
Lithium ion Batter	y DS751517					
2. Manufacturer of cell	l / battery					
Name Tig	erpow Battery	DongGuan CO	Ltd			
Address						
Phone						
Email						
Website						
3. Test laboratory of co	ell / halteru			wint a second control of the		
		national Group	Co. Ltd			
Address	, , , , , , , , , , , , , , , , , , ,					
Phone						
Email						
Website				MANAN SAL		
4. ID-number and date	e					
Unique test report identification number MMIXMY9M84037721 Date of te		Date of test r	t report 2017/02/22			
	reacombioscolescolesculous en de constante de la constante de			Zinina wa Usania e wasinina wazi a		
DESCRIPTION OF (CELL / BATTER	Ϋ́				
5. Mark the type of ce	ell/battery with an	"•"				
Lithium ion cell					Lithium metal cell	
X Lithium ion battery			hium me	etal battery		
Lithium hybrid t	battery					
6. Parameters					Cell	Battery
Mass in gram (g):			- Tour self theorem. The market sealth			3,2
Lithium ion: Indicate watt-hour rating (Wh):			······································		0,37	
Lithium metal: Indicate						0,01
Lithium hubrid ladicate lithium metal contect is gram (a) and watt hour rating (M/b):			(\ \ / \b).		g	

LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name of cell/battery (taken from field 1)

Polymer lithium ion Battery

7. Physical description of cell / battery				
prismatic				
8. Model numbers				
23862 TwiStar				
TESTS AND RESULTS				
9. List of tests conducted and results - Mark N/A, pass or fail with an "●"	N/A	pass	fail	
T1 - Altitude simulation	0	0	0	
T2 - Thermal Test	O	Q	0	
T3 - Vibration		0	0	
T4 - Shock		0		
T5 - External Short Circuit	0	0	0	
T6 - Impact / Crush	0			
T7 - Overcharge	0	0		
T8 - Forced Discharge				
for all above		\otimes		
10. Reference to assembled battery testing requirements		Τ		
			N/A	
11. Reference to the revised edition of the Manual of Tests and Criteria used and to amendments thereto				

LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name of cell/battery (taken from field 1)

Polymer lithium ion Battery

ADDITIONAL SUPPLIER INQUIRY

12. Quality management system for manufacturing cells / batteries Does the manufacturer of the cell/battery manufacture the products based on a documented quality management system according to transport regulations?	X	ES	NO
13. Are the following parameters exceeded? Lithium ion cell: more than 20 Wh Lithium ion battery: more than 100 Wh Lithium metal cell: more than 1 g Lithium Lithium metal battery: more than 2 g Lithium Lithium hybrid Battery: more than 1,5 g Lithium and/or more than 10 Wh	O _Y	ES	NOX

Check point 14 – 16 need to be answered when 13 has been ticked "YES":			
14. Does each cell / battery incorporates a safety venting device or is designed to preclude a violent rupture under normal conditions of carriage?	Y	ES	NO
15. Is each cell / battery equipped with an effective means of preventing external short circuits?	Y	ES	NO ON
16. Is each battery containing cells or series of cells connected in parallel equipped with effective means as necessary to prevent dangerous reverse current flow (e.g. diodes, fuses, etc.)?	Y	ES	NO
 Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion cells/batteries and lithium polymer cells/batteries 			
State of Charge (SoC) max. 30 %	O Y	ES	NO

CELLS/BATTERIES INSTALLED IN EQUIPMENT

18. Check point 18 needs to be answered when the cells / batteries are installed in articles:							
18.a) Only button cells enclosed?				NO X			
18.b) Number of enclosed cells (other than button cells)/batteries per equipment							
	Enclosed cells per equipment	Enclos	ed batt	eries pe	er equip	ment	1
When the equipment is intentionally active/switched on during transport e.g. data loggers:							
18.c) Confirmation that no dangerous amount of heat is emitted from the equipment				NO			
18.d) Confirmation that the equipment when transported by air fulfills the defined air transport standards for electromagnetic radiation according to DO-160			NO				

19. Place, Date	20. Title, Surname, First name	21. Company stamp and signature				
Bünde, 2019.11.26	Vieregge Thomas Head of Quality Assurance & Product Safty	P. M. Reyell GmbH				

Henschelstr. 20 3 32257 Bünde Tel.: (+49/0) 5223 (

