LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

N/A = Not Applicable

1. Name of cell / baltery					
Lithium ion Cell 14500					
2. Manufacturer of cell / baltery	2 Manufacturer of cell / hatteru				
The state of the s	Shantou Jinlongjie Electronics Co Ltd				
Address	Chaines children of Lia				
Phone					
Email					
Website					
Test laboratory of cell / battery					www.communication.com
Address					
Phone					
Email					
Website	Website Website				
4. ID-number and date					
Unique test report identification number				018/058/30	
DESCRIPTION OF CELL / BATTERY					
5. Mark the type of cell/battery with an	″ ●"				
Lithium ion cell	ım ion cell Lithium metal cell			metal cell	
Lithium ion battery	ion battery Lithium metal battery				
Lithium hybrid battery					
6. Parameters			Cell	Battery	
Mass in gram (g):				16,1	
Lithium ion: Indicate watt-hour rating (Wh):				1,48	
Lithium metal: Indicate lithium metal content in gram (g):					
Lithium hybrid: Indicate lithium metal content in gram (g) and watt-hour rating (Wh):					g

LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name of cell/battery (taken from field 1)

Polymer lithium ion Battery

7. Physical description of cell / battery		wantan yawan se wasana		
prismatic				
8. Model numbers				
24463 Mercedes G Class				
TESTS AND RESULTS				
9. List of tests conducted and results - Mark N/A, pass or fail with an "•"	N/A	pass	fail	
T1 - Altitude simulation	O	P833	()	
T2 - Thermal Test	8	8	A	
T3 - Vibration	A	A	A	
T4 - Shock	Image: Control of the	Ŏ	Ŏ	
T5 - External Short Circuit	Ö	Ŏ	Ŏ	
T6 - Impact / Crush	Ŏ	Ŏ	Ŏ	
T7 - Overcharge	Ŏ	Ŏ	Ŏ	
T8 - Forced Discharge	Ŏ	Ŏ	Ŏ	
for all above	Ŏ	\otimes	O	
	O	Ŏ	O	
10. Reference to assembled battery testing requirements		1	T	
			N/A	
11. Reference to the revised edition of the Manual of Tests and Criteria used and to amendments thereto				

LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name of cell/battery (taken from field 1)

Polymer lithium ion Battery

ADDITIONAL SUPPLIER INQUIRY

12. Quality management system for manufacturing cells / batteries Does the manufacturer of the cell/battery manufacture the products based on a documented quality management system according to transport regulations?	X	YES	NO
13. Are the following parameters exceeded? Lithium ion cell: more than 20 Wh Lithium ion battery: more than 100 Wh Lithium metal cell: more than 1 g Lithium Lithium metal battery: more than 2 g Lithium Lithium hybrid Battery: more than 1,5 g Lithium and/or more than 10 Wh		YES	NOX
Check point 14 – 16 need to be answered when 13 has been ticked "YES":			
14. Does each cell / battery incorporates a safety venting device or is designed to preclude a violent rupture under normal conditions of carriage?		YES	NO
15. Is each cell / battery equipped with an effective means of preventing external short circuits?	0	YES	NO
16. Is each battery containing cells or series of cells connected in parallel equipped with effective means as necessary to prevent dangerous reverse current flow (e.g. diodes, fuses, etc.)?	0	YES	NO
 Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion cells/batteries and lithium polymer cells/batteries 			
State of Charge (SoC) max. 30 %	0	YES	NO O

CELLS/BATTERIES INSTALLED IN EQUIPMENT

18. Check point 18 needs to be answered when the cells / batteries are installed in articles:					
18.a) Only b	ulton cells enclosed?			YES	NO (X)
18.b) Number of enclosed cells (other than button cells)/batteries per equipment					
	Enclosed cells per equipment	Enclosed batteries per equipment		1	
When the equipment is intentionally active/switched on during transport e.g. data loggers:					
18.c) Confirm	nation that no dangerous amount of heat is emitted	from the equipment	N/A	YES	NO
18.d) Confirm air tran	nation that the equipment when transported by air esport standards for electromagnetic radiation ac	fulfills the defined cording to DO-160	N/A	YES	NO

19. Place, Dale	20. Title, Surname, First name	21. Company stamp and signature
Bünde, 2019.11.26	Vieregge Thomas Head of Quality Assurance & Product Safty	in Mevell GmbH
		Henschelstr. 20-30

32257 Bünde Tel.: (+49/0) 5223 965-0

