# LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

N/A = Not Applicable

1. Name of c	ell / battery		**************************************				
Lithium ion Battery 18650							
2. Manufacturer of cell / baltery							
Name	Shantou Jinlongjie Electronics Co Ltd						
Address							
Phone							
Email							
Website							
Test laboratory of cell / battery							
Name  Shenzhen LCS Compliance and Testing Laboratory Co. Ltd							
Address		The state of the s					
Phone							
Email							
Website							
4. ID-number and date							
Unique test re	que test report identification number LCS180402259ASA		59ASA	Date of test report		2018/07/20	
DESCRIPTION OF CELL / BATTERY							
5. Mark the t	ype of cell/baltery with an	″•"					
Lithium	Lithium ion cell			Lithium metal cell			
Lithium ion battery			hium metal battery				
Lithium hybrid battery							
6. Parameters			Cell		Battery		
Mass in gram (g):					77,9		
Lithium ion: Indicate watt-hour rating (Wh):					8,88		
Lithium metal: Indicate lithium metal content in gram (g):							
Lithium hybrid: Indicate lithium metal content in gram (g) and watt-hour rating (Wh):					***************************************	g	



# LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name of cell/battery (taken from field 1)

Polymer lithium ion Battery

7. Physical description of cell / battery					
prismatic					
8. Model numbers					
24469 Snow Patrol					
TESTS AND RESULTS					
9. List of tests conducted and results - Mark N/A, pass or fail with an "•"	N/A	pass	fail		
T1 - Altitude simulation	9	$\sim$			
T2 - Thermal Test	2	2	2		
T3 - Vibration	9	9			
T4 - Shock	2	2	2		
T5 - External Short Circuit	Q	Q	Q		
T6 - Impact / Crush	Q	Q	Q		
T7 - Overcharge	Q	Q	Q		
T8 - Forced Discharge	0	0	0		
for all above	0	$\otimes$	0		
	0	0	0		
40 Perference to accomplisable to the second	VIII. COLOR DE LA COLOR DE		meter (1904) and an and an account that		
10. Reference to assembled battery testing requirements			T		
			N/A		
11. Reference to the revised edition of the Manual of Tests and Criteria used and to amendments thereto					

# LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3
OF MANUAL OF TESTS AND CRITERIA

Name of cell/battery (taken from field 1)

Polymer lithium ion Battery

## ADDITIONAL SUPPLIER INQUIRY

2. Quality management system for manufacturing cells / batteries  Does the manufacturer of the cell/battery manufacture the products based on a documented quality management system according to transport regulations?		YES	NO			
13. Are the following parameters exceeded?  Lithium ion cell: more than 20 Wh  Lithium ion battery: more than 100 Wh  Lithium metal cell: more than 1 g Lithium  Lithium metal battery: more than 2 g Lithium  Lithium hybrid Battery: more than 1,5 g Lithium and/or more than 10 Wh	$\bigcirc$	YES	NO X			
Check point 14 – 16 need to be answered when 13 has been ticked "YES":						
14. Does each cell / battery incorporates a safety venting device or is designed to preclude a violent rupture under normal conditions of carriage?		YES	NO			
<b>15.</b> Is each cell / battery equipped with an effective means of preventing external short circuits?		YES	NO (			
16. Is each battery containing cells or series of cells connected in parallel equipped with effective means as necessary to prevent dangerous reverse current flow (e.g. diodes, fuses, etc.)?	O	YES	NO			
<ol> <li>Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion cells/batteries and lithium polymer cells/batteries</li> </ol>						
State of Charge (SoC) max. 30 %	0	YES	NO O			

## CELLS/BATTERIES INSTALLED IN EQUIPMENT

40 Charlesial 40 and the transfer of the trans							
18. Check point 18 needs to be answered when the cells / ba	atteries are installed	l in arti	cles:				
18.a) Only bulton cells enclosed?				YES	NO	(X)	
18.b) Number of enclosed cells (other than button cells)/batteries per equipment							
Enclosed cells per equipment Enclosed batteries per equi			er equip	ment	1		
When the equipment is intentionally active/switched on during transport e.g. data loggers:							
18.c) Confirmation that no dangerous amount of heat is emitted from the equipment X N/A YES					ΝΟ		
18.d) Confirmation that the equipment when transported by air air transport standards for electromagnetic radiation acc	fulfills the defined cording to DO-160	X	N/A		YES	ΝО	
						-	-

19. Place, Date	20. Title, Surname, First name	21. Company stamp and signature
Bünde, 2019.11.26	Vieregge Thomas Head of Quality Assurance & Product Safty	1. Revell Gmbr.
		3229/05223 900

3225/ 5223 ( Tel.: (+49/0) 5223 (

