### LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

N/A = Not Applicable

1. Name of ce	ll / battery						
Lithium ion	Cell 14500						
			istorio assessi ai a Compositorio de la compositori				
	er of cell / battery						
Name	Shantou Jinlongji	e Electronics C	o Ltd				
Address							
Phone			Hara Contra				
Email							
Website							
3. Test laborat	ory of cell / baltery				***************************************		
Name	Shenzhen LCS Co	ompliance Testi	ng Laborato	ry Co. Ltd			
Address	3,10,12,13,112,03,00	- Pilando i Cott	g Lastrato	., co. ata			
Phone							
Email							
Website							
***************************************							
4. ID-number	and date					*	mumile to the second
Unique test rep	Unique test report identification number LSC180503060ASA		Date of test report		2018/05/30		
	N OF CELL / BATTER ipe of cell/battery with an						
X Lithium ion cell				Lithium metal cell			
Lithium ion battery			Li	Lithium metal battery			
Lithium	hybrid ballery						
6. Parameters	>				Cell		Baltery
Mass in gram (g):				Cett		16,1	
Lithium ion: Indicate watt-hour rating (Wh):						1,48	
		<del></del>					1,40
	Indicate lithium metal con			- Control of the Cont			
Lithium hybrid	: Indicate lithium metal cor	ntent in gram (g) and	l watt-hour ratin	g (Wh):			



## LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name of cell/battery (taken from field 1)

Polymer lithium ion Battery

7. Physical description of cell / battery		· · · · · · · · · · · · · · · · · · ·			
prismatic					
8. Model numbers					
24474 Red Scorpion					
TESTS AND RESULTS					
		<u> </u>	г		
9. List of tests conducted and results - Mark N/A, pass or fail with an "●"	N/A	pass	fail		
T1 - Altitude simulation	O	O	0		
T2 - Thermal Test	O	0	0		
T3 - Vibration	0				
T4 - Shock	0	0			
T5 - External Short Circuit	0				
T6 - Impact / Crush		0			
T7 - Overcharge	0	0	O		
T8 - Forced Discharge	Ŏ	Ŏ	Ŏ		
for all above	O	X	O		
	Ŏ	Ŏ	Ŏ		
10. Reference to assembled battery testing requirements					
			N/A		
			N/A		
11. Reference to the revised edition of the Manual of Tests and Criteria used and to amendments thereto					

# LITHIUM CELL/BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name of cell/battery (taken from field 1)

Polymer lithium ion Battery

### ADDITIONAL SUPPLIER INQUIRY

12. Quality management system for manufacturing cells / batteries Does the manufacturer of the cell/battery manufacture the products based on a documented quality management system according to transport regulations?	X YES	NO
13. Are the following parameters exceeded?  Lithium ion cell: more than 20 Wh  Lithium ion battery: more than 100 Wh  Lithium metal cell: more than 1 g Lithium  Lithium metal battery: more than 2 g Lithium  Lithium hybrid Battery: more than 1,5 g Lithium and/or more than 10 Wh	YES	NOX
Check point 14 – 16 need to be answered when 13 has been ticked "YES":		
14. Does each cell / battery incorporates a safety venting device or is designed to preclude a violent rupture under normal conditions of carriage?	YES	NO
15. Is each cell / battery equipped with an effective means of preventing external short circuits?	YES	NO O
16. Is each battery containing cells or series of cells connected in parallel equipped with effective means as necessary to prevent dangerous reverse current flow (e.g. diodes, fuses, etc.)?	YES	NO
<ol> <li>Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion cells/batteries and lithium polymer cells/batteries</li> </ol>		
State of Charge (SoC) max. 30 %	YES	NO

#### CELLS/BATTERIES INSTALLED IN EQUIPMENT

18. Check p	oint 18 needs to be answered when the cells / batte	eries are installed i	in artic	cles:				
18.a) Only bulton cells enclosed?					YES	NO	X	
18.b) Numbe	er of enclosed cells (other than button cells)/batterie	s per equipment						
	Enclosed cells per equipment	Enclose	ed batt	eries pe	er equip	ment	1	
When the equipment is intentionally active/switched on during transport e.g. data loggers:								
18.c) Confirmation that no dangerous amount of heat is emitted from the equipment X N/A YES				YES	NO			
18.d) Confirmation that the equipment when transported by air fulfills the defined air transport standards for electromagnetic radiation according to DO-160				YES	NO			

19. Place, Date	20. Title, Surname, First name	21. Company stamp and signature
Bünde, 2019.11.26	Vieregge Thomas Head of Quality Assurance & Product Safty	Revell GmbH

32257 Bunde 32257 Bunde Tel.: (+49/0) 5223 965-0

